


# SUBMITTAL DATA FLOW DIVERTER

## FD SERIES CLASS 250/300



MAXIMUM OPERATING CONDITIONS	
Working Temperature	250 Deg F
Working Pressure	300 PSI

MATERIALS OF CONSTRUCTION	
Body	Steel
Strainer	Stainless Steel

MODEL	SYSTEM CONN.	PUMP CONN.	DIMENSIONS					
			A	B	C	D	E	F
1.5 X 1.5	1.5"	1.5"	7.13"	7.88"	7.13"	12.88"	13.06"	5.93"
2 X 1.25		1.25"						
2 X 1.5	2"	1.5"						
2 X 2		2"						
2.5 X 1.5	2.5"	1.5"						
2.5 X 2		2"						
2.5 X 2.5		2.5"						
3 X 1.5	3"	1.5"						
3 X 2		2"						
3 X 2.5		2.5"						
3 X 3		3"						
4 X 1.5	4"	1.5"						
4 X 2		2"						
4 X 2.5		2.5"						
4 X 3		3"						
4 X 4		4"						
5 X 2.5	5"	2.5"						
5 X 3		3"						
5 X 4		4"						
5 X 5		5"						
6 X 2.5	6"	2.5"						
6 X 3		3"						
6 X 4		4"						
6 X 5		5"						
6 X 6		6"						
8 X 4		4"						
8 X 5	8"	5"						
8 X 6		6"						
8 X 8		8"						
10 X 6		6"						
10 X 8	10"	8"						
10 X 10		10"						
12 X 8		8"						
12 X 10	12"	10"						
12 X 12		12"						
14 X 10	14"	10"						
14 X 12		12"						
14 X 14		14"						
16 X 10	16"	10"						
16 X 12		12"						
16 X 14		14"						

JOB NAME \_\_\_\_\_  
 LOCATION \_\_\_\_\_  
 \_\_\_\_\_  
 CONTRACTOR \_\_\_\_\_  
 CONTRACTOR P.O. NO. \_\_\_\_\_

ITEMS	QUANTITY
_____	_____
_____	_____
_____	_____
_____	_____
_____	_____



1005 E. Houston  
 Broken Arrow, OK 74012  
 Toll Free: 866-204-5229  
 PH: 918-317-0401  
 FAX: 918-317-0407  
 www.wheatleyhvac.com  
 e-mail: sales@globalflowproducts.com